

FAGA MASTER

- ✓ Unique tread design providing ultimate performance.
- ✓ Extra tread quantity than other competitors ensures longer service life. (tread quantity 40% by weight)
- ✓ Wider tread contact area. Best footprint. (even wear, better load stability, high safety)
- ✓ Premium quality natural rubber based tread compound. (Long service life, high traction, low rolling resistance)
- ✓ 3 stage construction with low heat build up soft center layer. (Fit for long hour operations. Better mobility and comfort.)
- ✓ Steel creel bead reinforced high hardness base. (best rim fit, zero rim slip)
- ✓ Zero Down time.



- Available in 3 stage Premium / Standard / Economy variants.
- Standard (STD), Clip On / Easy fit (LOC), Non Marking (white, gray) are available.
- All tyres are designed and produced according to the ETRTO standards.

SPECIFICATIONS

Ø	TYRE SIZE	PROFILE	RIM SIZE	TYRE DIMENSIONS (+/-2%)		LOAD CAPACITY (kg)				
				Diameter mm	Width mm	FORKLIFTS (25km/h)		OTHER VEHICLES (TRAILERS)		
						Load Wheel	Steering Wheel	20km/h	10km/h	6km/h
8"	4.00 X 8	STD	3.00D-8	406	104	950	730	730	860	950
	4.00 X 8	CLIP	3.00D-8	406	104	950	730	730	860	950
	5.00 X 8	STD	3.00D-8	451	117	1415	1090	1090	1285	1415
	5.00 X 8	CLIP	3.00D-8	451	117	1415	1090	1090	1285	1415
	15 X 4.5 - 8 (125/75-8)	STD	3.00D-8	378	106	1040	800	800	940	1040
	15 X 4.5 - 8 (125/75-8)	CLIP	3.00D-8	378	106	1040	800	800	940	1040
	16 X 6-8 (150/75-8)	STD	4.33R-8	418	150	1455	1120	1120	1320	1455
	16 X 6-8 (150/75-8)	CLIP	4.33R-8	418	150	1455	1120	1120	1320	1455
	18 X 7-8 (180/70-8)	STD	4.33R-8	455	150	2145	1650	1650	1945	1245
18 X 7-8 (180/70-8)	CLIP	4.33R-8	455	150	2145	1650	1650	1945	1245	
9"	140/55-9	STD	4.00E-9	380	130	1170	900	900	1060	1170
	140/55-9	CLIP	4.00E-9	380	130	1170	900	900	1060	1170
	6.00 X 9	STD	4.00E-9	518	140	1885	1450	1450	1710	1885
	6.00 X 9	CLIP	4.00E-9	518	140	1885	1450	1450	1710	1885
	21 X 8-9 (200/75-9)	STD	6.00E-9	522	180	2755	2120	2120	2505	2755
	21 X 8-9 (200/75-9)	CLIP	6.00E-9	522	180	2755	2120	2120	2505	2755
10"	200/50-10	STD	6.50F-10	457	193	2470	1900	1900	2040	2470
	200/50-10	CLIP	6.50F-10	457	193	2470	1900	1900	2040	2470
	6.50 X 10	STD	5.00F-10	571	154	2340	1800	1800	2125	2340
	6.50 X 10	CLIP	5.00F-10	571	154	2340	1800	1800	2125	2340
	23 X 9-10 (225/75-10)	STD	6.50F-10	585	188	3445	2650	2650	3125	3445
	23 X 9-10 (225/75-10)	CLIP	6.50F-10	585	188	3445	2650	2650	3125	3445
12"	7.00 X 12	STD	5.00S-12	653	166	2920	2240	2240	2640	2920
	7.00 X 12	CLIP	5.00S-12	653	166	2920	2240	2240	2640	2920
	23 X 10-12	STD	8.00G-12	590	230	3770	2900	2900	3420	3770
	23 X 10-12	CLIP	8.00G-12	590	230	3770	2900	2900	3420	3770
	27 X 10-12	STD	8.00G-12	675	240	3900	3000	3000	3450	3900
	27 X 10-12	CLIP	8.00G-12	675	240	3900	3000	3000	3450	3900
15"	2.50 X 15 (250/70-15)	STD	7.0-15	715	215	4750	3650	3650	4300	4750
	2.50 X 15 (250/70-15)	CLIP	7.0-15	715	215	4750	3650	3650	4300	4750
	8.25 X 15	STD	6.5-15	805	195	4150	3650	3650	4300	4750
	8.25 X 15	CLIP	6.5-15	805	195	4150	3650	3650	4300	4750
	3.00 X 15 (315/70-15)	STD	8.0-15	810	245	5850	4500	4500	5310	5850
	3.00 X 15 (315/70-15)	CLIP	8.0-15	810	245	5850	4500	4500	5310	5850
	28 X 9 - 15 (8.15-15)	STD	7.0-15	695	210	3445	2650	2650	3125	3445
	28 X 9 - 15 (8.15-15)	CLIP	7.0-15	695	210	3445	2650	2650	3125	3445
	28 X 12.5-15	STD	9.75-15	700	285	5525	4250	4250	5015	5525
	28 X 12.5-15	CLIP	9.75-15	700	285	5525	4250	4250	5015	5525
	355/65-15 (3.50-15)	STD	9.75-15	810	290	7800	6000	6000	7085	7800
	355/65-15 (3.50-15)	CLIP	9.75-15	810	290	7800	6000	6000	7085	7800

